

Cerrazzo grout

Grout for terrazzo flooring

Description

Cerrazzo grout is one of the ingredients of Cipy's Cerrazzo floorings. Cerrazzo grout is a two component viscous material which is used for filling up the porosities of Cerrazzo matrix.

Uses

- Cerrazzo grout is used for grouting the pores of the Cerrazzo layer.

Key features

- Easy to mix and pour
- Hard and polishable

Directions to use

Cerrazzo Grout

The grinding process using diamond grit grinders, exposes the voids caused by air bubbles in the Cerrazzo matrix and aggregate pop-outs, which are then filled up with Cerrazzo Grout. Cerrazzo Grout is a two component, viscous material containing resin and hardener. Unpack the two components and mix thoroughly using a slow speed electric mixer for 2-3 minutes. The grout is applied using a flat rubber squeegee or grout trowel and allowed to cure overnight. Re-grouting may be required if the voids still remain on the surface.

Properties

Type	: Epoxy-polyamine
Ratio of mixing	: 4:1 by weight
Potlife	: 45-60 min
Cure	: 24 hours

Packaging

Cerrazzo grout is available in pre-weighed kits and has maximum shelf life of 12 months in the unopened containers.

Storage and handling

The product should be stored in accordance with national regulations. It should be kept in a cool, well ventilated area, away from heat, direct sunlight, sparks and children. It contains inflammable solvents. Handle with care.

Health and safety precautions

Please refer to MSDS. Observe reasonable care and employ ordinary hygienic principles such as washing the hands with soap and water before eating or smoking. It is recommended to wear gloves, goggles and nose masks while application. In case of splashes on the skin, dampen the cloth with thinner PUT 503 and wipe the hands with the cloth. Wash then with soap and water. Dried film is non-toxic. In case of contact with eyes, rinse with plenty of water and seek medical advice. In case of continuous exposure to vapour, the applicator should be immediately moved to get fresh air. The disposal of excess or waste material should be carried out in accordance with the local legislations.

Cerrazzo grout

Grout for terrazzo flooring

Disclaimer

All information contained in this data sheet is given to the best of our knowledge but no warranty is made with respect thereto. This data sheet becomes invalid as soon as a new edition has been published. Please contact us for latest edition. Description and advice regarding Cipy's products are based on long term field and laboratory tests carried out by us. No condition of warranty is given covering the results from the use of materials in the circumstances of any particular application, because the storage, handling and application of the materials are beyond our control

Ref.: CPPL/06-21/0126/R-1



Cipy Polyurethanes Pvt Ltd

T-127, MIDC, Bhosari, Pune - 411 026

Tel. +91-20-66316400 / Fax : +91-20-66316460

Email : info@cipypolyurethane.com

