





# PU Concrete floorings

for hygienic environments

# Duracrete Flouring Systems

**SPECIALIZED FLOOR COATINGS** 





With its excellence in the industry for over 45 years, Dr. Cipy today is recognized as the leading manufacturer of specialist resin flooring products.

Dr. Cipy successfully manufactures seamless terrazzo, antimicrobial Polyurethane flooring, decorative resin flooring, self-levelling floor screeds, corrosion protection systems, static dissipative flooring, artistic flooring finishes and waterproof car park deck coatings which cater specifically to the Indian climate. With the support of our state of the art manufacturing plants, which are strategically placed to provide consistent high standards of product and service across the country. We ensure our clients'

satisfaction from the best in modern technology with our strong focus on research and development and the consistent innovation of new and improved products. Our continuous commitment to be environmentally conscious and introduce greener flooring products is in conjunction with our company policy of environmental care and protection. IGBC certification is the endorsement of our environment consciousness. Dr. Cipy is a Pidilite Group product brand, offering a truly quality service to customers.

Duracrete is based on a unique chemistry where urethane and cement are fused to form a thick, self-levelling flooring that is resistant to thermal shocks, aggressive chemicals, impact loads and vehicular traffic.

Dr. Cipy's Duracrete has withstood the testing times on heavily trafficked industrial floors. Duracrete is designed to last and perform in any industry which encounter physical and chemical abuses. Duracrete flooring systems are installed nationwide by Dr. Cipy's authorized applicators who have undergone intensive training at Dr. Cipy's R&D centre. Strict food safety requirements in F&B

require floorings to be clean and serviceable. Duracrete is seamless, hygienic, odourless and does not support bacterial growth. Like stainless steel substrates, all Duracrete floors can be effectively sanitized by steam cleaning to a standard comparable to stainless steel.



## The features that will floor you.

A range of purposely designed floors for every industry that will not let you down, even after years of abuse. The versatile Duracrete range of flooring systems can be tailored to suit specific requirements in a F&B industry. A range that virtually help you to be successful.











Thermal Shock Resistant





Static Dissipative













Antimicrobial Certified



**HACCP** Certified



## **Application**

Food & Beverage plants

Cold Storages

Meat processing plants

Dairies

Commercial kitchens

Bakeries

Pharma industries

Breweries


Engineering & Automobiles

Defence

## **Duracrete MD**

Duracrete MD is a four-component PU concrete flooring recommended as robust floorings in food and beverage industries. Duracrete MD is a self smoothing polyurethane concrete flooring system designed

to provide outstanding abrasion and chemical resistance and is generally applied at thicknesses 4-6 mm. Duracrete MD is also available in Antimicrobial Version known as Duracrete MD-AM.



#### Technical Parameters of Duracrete MD

Compressive Strength ASTM C 579	≥ 40 Mpa
Tensile strength ASTM D 638	≥ 5 MPa
Flexural strength ASTM D 790	≥ 20 MPa
Abrasion resistance ASTM D 4060	≤ 50mg loss
Service te mperature (for 4mm)	-15° to +80° C



## **Areas of Application**


- Fond processing industries
- Beverage plants
- Confectionaries
- Dairies
- Process industries
- Automobiles
- Defence



## Duracrete ESD 2000

Duracrete ESD 2000 is a five component PU ESD flooring recommended for the most demanding application in the industry. Duracrete ESD is a water based, polyurethane flooring system

designed to provide an extremely abrasion and chemical resistant static dissipative floor topping.



#### Technical Parameters of Duracrete ESD 2000

Compressive Strength ASTM C 579	≥ 40 Mpa
Tensile strength ASTM D 638	≥8 Mpa
Flexural strength ASTM D 790	≥ 20 Mpa
Abrasion resistance ASTM D 4060	≤ 50 mg loss
Service te mperature (for 4mm)	-5° to 70° C
Surface Resistivity	10 <sup>6</sup> to 10 <sup>9</sup> Ohm



- Hospital OT.
- Automobile Paint Shop
- Petrochemical Units
- Ammunition Depot
- Airforce Hanger
- Electronics Industry


Layers	Duracrete	Thickness	Smouth or Texture	Skid value
2	Duracrete MD	4mm-6mm	Flow grade, Smooth	40-70

Layers	Duracrete	Thickness	Smouth or Texture	Skid value
2	Duracrete ESD	2mm	Smooth	40-70

## **Duracrete HD**

Duracrete HD is a four-component PU concrete flooring recommended for the most demanding applications in the food and beverage industries. Duracrete HD is an anti-skid polyurethane concrete flooring system designed to provide outstanding thermal

shock resistance and is generally applied at thicknesses 6-9 mm. Duracrete HD is also available in Antimicrobial Version known as Duracrete HD-AM.



#### Technical Parameters of Duracrete HD-AM

Compressive Strength ASTM C 579	≥ 50 Mpa
Tensile strength ASTM D 638	≥ 5 Mpa
Flexural strength ASTM D 790	≥ 15 Mpa
Abrasion resistance ASTM D 4060	≤ 40 mg loss
Service temperature	-20°C to 90°C (for 6 mm) -40°C to 120°C (for 9mm)
Shore D Hardness (ASTM D 2240)	> 80



## **Areas of Application**

- Fond processing industries
- Beverage plants
- Confectionaries
- Abbottairs
- Cold storage roums
- Dairies
- Commercial and industrial kitchens

Layers	Duracrete	Thickness	Smooth or Texture	Skid value
2	Duracrete HD	6mm	Medium- Heavy Texture	40-70
2	Duracrete HD	9mm	Medium- Heavy Texture	40-70

## **COVING**




#### **Duracove**

Duracove is a cost effective, three components, trowel applied, Polyurethane coving mortar. It is designed for use with Duracrete range of flooring systems to give a seamless finish for hygienic areas.

Duracove is used as a Mortar/ Screed for horizontal and vertical covings in pharma and food processing industries.

#### **Technical Parameters**

Compressive Strength ASTM D 695	40- 45 Mpa
Tensile strength ASTM D 638	3-4 Mpa
Flexural strength ASTM D 790	11-14 Mpa



#### Duracove TC

#### Technical Parameters

Solid Content (ASTM D 2369)	≥ 70%
DFT (ASTM D 7091)	140 micron
Tensile Strength (ASTM D 638)	6-8 MPa
Abrasion Resistance (ASTM D 4060)	75-90 mg loss



## KULKARNI LABORATORY & QUALITY MANAGEMENT SERVICES

Office: E-1 Omega Heritage, Chavan Baug, DSK Vishwa Road, Dhayari, Pune – 411041.

Contact: (020) 24690107. Mob: 9850982510/ 9763050611. E-mail: klqmslab@gmail.com

Ref No :KLQMS/CPPL/10	Date: 18.06.2019
Customer Name & Address:	Page - 1 of 1
To,	Sample Name : Duracrete HD
M/S. Cipy Polyurethanes Pvt. Ltd.	B.No.: Resin – SFG/BH0361, Hardner – SFG/BH0370
T - 127, M.I.D.C, Bhosari	Sample Given by: Customer
Pune - 411026	Customer Reference : CPPL/TEST/02
	Sample received date: 27.05.2019

#### **TEST REPORT**

Sr.No.	Test Parameter	Specification	Result	Test Method
1.	Volume Solids (%)	≥ 98	98.10	ASTM D 2697
2.	Adhesion Pull off Test (Mpa)	≥2	3.2	ASTM D 4541
3.	Tensile Strength (Mpa)	≥5	6.5	ASTM D 638
4.	Flexural Strength (Mpa)	≥ 15	17.2	ASTM D 790
5.	Compressive Strength (Mpa)	≥ 50	52	ASTM C 579
6.	Abrasion Resistance (mg loss)	≤ 40	31	ASTM D 4060
7.	Pendulum test ,Slip Resistance	40 - 70	52	BS 8204
8.	Water absorption (%)	≤1	0.03	ASTM D 570
9.	Shore D Hardness	≥ 80	82	ASTM D 2240







## KULKARNI LABORATORY & QUALITY MANAGEMENT SERVICES



Office: E-1 Omega Heritage, Chavan Baug, DSK Vishwa Road, Dhayari, Pune – 411041.

Contact: (020) 24690107. Mob: 9850982510/ 9763050611. E-mail: klqmslab@gmail.com

Ref No :KLQMS/CPPL/11	Date: 18.06.2019
Customer Name & Address:	Page - 1 of 1
То,	Sample Name : Duracrete MD
M/S. Cipy Polyurethanes Pvt. Ltd.	B.No.: Resin – SFG/BH0037, Hardner – SFG/BH0008
T-127, M.I.D.C, Bhosari	Sample Given by: Customer
Pune - 411026	Customer Reference : CPPL/TEST/02
	Sample received date: 27.05.2019

#### **TEST REPORT**

Sr.No.	Test Parameter	Specification	Result	Test Method
1.	Adhesion Pull off Test (Mpa)	≥ 2	2.7	ASTM D 4541
2.	Tensile Strength (Mpa)	≥ 5	5.5	ASTM D 638
3.	Flexural Strength (Mpa)	≥ 20	21.2	ASTM D 790
4.	Compressive Strength (Mpa)	≥ 40	42	ASTM C 579
5.	Abrasion Resistance (mg loss)	≤ 50	43	ASTM D 4060
6.	Pendulum test ,Slip Resistance	40 - 70	48	BS 8204
7.	Water absorption (%)	≤1	0.05	ASTM D 570
8.	Shore D Hardness	≥ 75	80	ASTM D 2240







Format No: SALLGN/TRF/GEN Issue No:01, Issue Date: 01-04-2017 Page 1 of 4

#### **TEST REPORT**

Test Report Issued To:

CIPY POLYURETHANES PVT. LTD.

CIN:U74220DL1998PLC092698

T 127 M.I.D.C.,, BHOSARI,, PUNE, MAHARASHTRA, INDIA, 411026,

Test Report No: M191211008/M191211008-1


**Date of Issue:** 31-Dec-2019

Sample Booking/Receipt Date: 11-Dec-2019
Date of Start of Testing: 30-Dec-2019
Date of Completion of Test: 30-Dec-2019

Customer Relationship Number

M28686

Sample Description : DURACRETE HD



Customer Reference No :

E-Mail:

PO/SR/0498/19-20 DT. 06/11/2019

Kind Attention: MR.DEEPAK AKOLE

info@cipypolyurethane.com

Contact No:

9823191914

Sample Condition : GOOD CONDITION

Sample Quantity (Approx) : 6 NOS

Sample Size (Approx) :

SAMPLE NOT DRAWN BY OUR LABORATORY. THE RESULTS RELATE ONLY TO THE ITEMS TESTED

Digitally signed by PRASHANTS KUMAR TIWARI 15.50-53-05.30

ULR-TC631419000067076F

Authencity of report can be verified by mail at <a href="mailto:verification@spectrolab.in">verification@spectrolab.in</a>

This is a Digitally Signed Report and hence doesn't require Physical Signature.

Spectro Analytical Labs Limited S-1, GNEPIP, Surajpur Industrial Area,Phase-V, Kasna, Greater Noida-201308 (India)

Phone: +91-120-2341250,2341251 || URL: www.spectro.in || Email: care@spectro.in



Format No: SALLGN/TRF/GEN
Issue No: 01 Issue Date: 01 04

Page 4 of 4

Report No. M191211008/M191211008-1

#### 8. SUMMARY OF RESULTS

The system has been evaluated in accordance with BS 476 Part 7

#### Observations

Specimen No.	1	2	3	4	5	6
Distance, mm	Time to travel distance (Min.: Sec.)					
75	0:16	0:21	0:18	0:23	0:20	0:24
165	0:27	0:29	0:30	0:32	0:26	0:33
190	0:38	0:40	0:42	0:43	0:39	0:41
215	0:50	0:52	0:55	0:54	0:51	0:53
240	1:09	1:14	1:16	1:10	1:17	1:12
265	1:29	1:33	1:37	1:34	1:36	1:29
455	1:46	1:52	1:55	1:53	1:49	1:50
710	1:56	2:04	2:09	2:07	2:01	1:59

	Flame Spread, mm					
Specimen No.	1	2	3	4	5	6
At 1.5 Minutes	260	280	270	265	285	280
Final Flame Spread	740	735	750	730	710	725

Result: The tested specimen qualified for Class 3 as per BS 476 Part 7.





-- End of Test Report --

ULR-TC631419000067076F



**Authorised Signatory** 

Spectro Analytical Labs Limited

S-1, GNEPIP, Surajpur Industrial Area, Phase-V, Kasna, Greater Noida-201308 (India)

Phone: +91-120-2341250,2341251 || URL: www.spectro.in || Email: care@spectro.in



Format No: SALLGN/TRF/GEN Issue No:01. Issue Date: 01-04-201 Page 1 of 4

#### CIN:U74220DL1998PLC092698

Test Report Issued To:

CIPY POLYURETHANES PVT. LTD.

T 127 M.I.D.C.,, BHOSARI,, PUNE, MAHARASHTRA, INDIA, 411026,

**TEST REPORT** 

M191211008/M191211008-2 Test Report No:

Date of Issue: 31-Dec-2019

Sample Booking/Receipt Date: 11-Dec-2019 Date of Start of Testing: 31-Dec-2019 Date of Completion of Test:

31-Dec-2019

**Customer Relationship Number** 

M28686

Sample Description: DURACRETE MD



Customer Reference No :

Sample Condition :

PO/SR/0498/19-20 DT. 06/11/2019

Kind Attention MR.DEEPAK AKOLE

E-Mail: info@cipypolyurethane.com Contact No

9823191914

Sample Quantity (Approx):

GOOD CONDITION

Sample Size (Approx): SAMPLE NOT DRAWN BY OUR LABORATORY. THE RESULTS RELATE ONLY TO THE ITEMS TESTED

ULR-TC631419000067079F

Authencity of report can be verified by mail at <a href="mailto:verification@spectrolab.in">verification@spectrolab.in</a>

This is a Digitally Signed Report and hence doesn't require Physical Signature.

Spectro Analytical Labs Limited S-1, GNEPIP, Surajpur Industrial Area, Phase-V, Kasna, Greater Noida-201308 (India)

**Phone**: +91-120-2341250,2341251 || **URL**: www.spectro.in || **Email**: care@spectro.in

BIS & DDA Approved, ISO 9001:2015, ISO 14001:2015 & ISO 45001:2018 Certified Laboratory Please refer to our Website http://www.spectro.in/spectro-policies.html for Terms & Condition



Format No: SALLGN/TRF/GEN

Page 4 of 4 Report No. M191211008/M191211008-2

#### 8. SUMMARY OF RESULTS

The system has been evaluated in accordance with BS 476 Part 7

Observations						
Specimen No.	1	2	3	4	5	6
Distance, mm	Time to travel distance (Min.: Sec.)					
75	0:15	0:18	0:21	0:25	0:22	0:20
165	0:29	0:31	0:30	0:36	0:34	0:33
190	0:41	0:39	0:43	0:45	0:47	0:46
215	0:53	0:56	0:58	0:59	1:01	1:06
240	1:12	1:15	1:21	1:23	1:20	1:24
265	1:25	1:27	1:32	1:30	1:31	1:36
455	1:33	1:40	1:37	1:38	1:41	1:45
710	1:45	1:48	1:46	1:42	1:47	1:51

	Flame Spread, mm					
Specimen No.	1	2	3	4	5	6
At 1.5 Minutes	260	275	280	265	270	265
Final Flame Spread	720	745	730	745	755	750

Result: The tested specimen qualified for Class 3 as per BS 476 Part 7.



-- End of Test Report --






Spectro Analytical Labs Limited

Analyst Signature

S-1, GNEPIP, Surajpur Industrial Area, Phase-V, Kasna, Greater Noida-201308 (India)

Phone: +91-120-2341250,2341251 || URL: www.spectro.in || Email: care@spectro.in







Confederation of Indian Industry

#### CII-Green Products and Services Council

hereby certifies that

#### **DURACRETE MD**

(GPCPU128008)

Manufactured by Cipy Polyurethanes Private Limited at their plant in Bhosari Pune, Maharashtra meets the requirements of GreenPro Certification and qualifies as Green Product.

This certification is valid till December 2022

Jamshvd N Godrei

ParasuRaman R

K S Venkatagiri Executive Director, CII-Godrej GBC

Chairman, CII-Green Products & Services Council









Chairman, CII-Godrej GBC



#### CII-Green Products and Services Council

hereby certifies that

#### **DURACRETE ESD 2000**

(GPCPU128011)

Manufactured by Cipy Polyurethanes Private Limited at their plant in Bhosari Pune, Maharashtra meets the requirements of GreenPro Certification and

qualifies as Green Product.

This certification is valid till **December 2022** 

Jamshyd N Godrej


Chairman, CII-Green Products & Services Council







## Colour Chart





BASALT GREY RAL 7012



PURE GREEN RAL 6037

# Duracrete Clientele

Meyer Pharma, Bangalore	Sterlite Industries, Aurangabad			
SRF, Dahej	Parekh Agro, Yavat			
Flex Foods, Bangalore	Toshiba, Pune			
Emami, Kandala	Tata Motors, Pimpri			
Grannules India, A.P	Automotive Axles Ltd., Bangalore			
Varun Beverages, Sandila	Toyota Kirloskar, Bangalore			
Varun Beverages, Bihar	Lulu International Shopping Mall, Kochi			
Varun Beverages, Begusaria	Bharat Bijlee Ltd., Mumbai			
Baskin Robin, Pune	BARC – Trombay			
Coke, Tirupati	Crompton Greaves - Bhopal			
Coke, Shreekalahasti	Carriage & Wagon Workshop			
Hansa (Excelsis Energy Pvt Ltd)	Kellogg India Pvt Ltd.,			
Mazda Foods	Mother Dairy Foods Processing Ltd.,			
Vijayganga Hospital	Serum Institute of Packaging			
Akshaya Patra, Hyderabad	ITC Ltd.			
Singhania Foods, Hyderabad	Sandoz Pvt Ltd., Mumbai			
Dukes Foods, Hyderabad	Glaxosmithkline			
Dodla Dairy, Hyderabad	Makson Nutrition Food Pvt Ltd.,			
Honda 2Wheelers, Bangalore	Motor Industries Co (MICO)			
Brakes India,Chennai	AT & S India Pvt Ltd.,			
Coca-Cola -Guwahati / Khurda / Siliguri	Cico Middle East, Qatar			
Aarti Industry, Dahej	Aljabor Trading Co., Qatar			
Aarti Industry Ankleshwar	Abu Dhabi Medical Industries, Dubai			
Alpala Ltd., Silvasa	Global Safety & Civil Supplies, Fiji			
Sterlite Technologies, Vapi	Eczacıbasi-Koramic, Istanbul			
Hindustan Unilever, Mumbai	Mill Mechanical Services, Dubai			



# Specialized flour coatings for

Automobiles

Auto Components

White Goods

Pharma

Car Parks

Hospitals and Healthcare

Airports

Епдіпеегіпд

Chemicals & Fertilizers

Defense



#### Pidilite Industries Ltd.

Dr. Cipy office,

T-127, MIDC, Bhosari, Рипе - 411П26. Maharashtra(MH), India.

+91 20 66316400

drcipy@pidilite.com

www.drcipy.com